POWER 3-in-1

Wall-mounted touchless basin tap with concealed connections

Water • Soap • Hand drying



Dimensioned drawing



Dimensions in mm: width 365; dimension along the arm 245, as shown. Catalogue illustration; not to scale.

Four finish options

Chrome | Brushed inox | Brushed gold | Matt black

Finishes follow the wall-mounted variant chart. Colour swatches are illustrative.

POWER 3-in-1

Wall-mounted touchless basin tap with concealed connections

Technical specifications

Functions	Touchless water delivery, soap dispensing and hand drying
Installation	Wall-mounted spout with concealed connections
Construction materials	304 stainless steel and brass
Control / sensing range	Infrared sensors / 3-12 cm
Power supply	220-240 V AC, 50/60 Hz; power supply unit included
Maximum power consumption	1000 W
Hand dryer motor	Brushless
Air speed	Up to 80 m/s
Drying time	Approx. 15-20 s; indicative value
Maximum water run time	60 s
Water connections	1/2 inch
Operating pressure	1-8 bar
Ingress protection rating	IPX4
Room humidity	Below 80%
Soap reservoir capacity	3000 ml (3 L)
Soap type	Suitable liquid or foaming soap, as specified in the manual; no gel
Minimum basin bowl depth	100 mm
Warranty	2 years

Installation planning and equipment

System includes the 3-in-1 tap, dispensing system with 3 L reservoir, hand dryer and power supply unit. Provide space for hoses and modules, with access for servicing and soap refilling. Position all three operating zones over the basin. A 1/2-inch water mixer is available separately.

Data scope: based on current catalogue descriptions for the wall-mounted versions and the chrome variant drawing. Concealed installation depth, wall opening diameter, module dimensions, water flow rate, soap dose and noise level are not specified in the available documentation. Confirm these before building the enclosure. This sheet does not replace the installation manual.

Source: STELLMAN® POWER 3-in-1 wall-mounted catalogue data and dimensioned drawing. Distribution: neogran.pl. Confirm availability of individual finishes when ordering.